

常规产品电性能参数

型号	标称值 25°C (K Ω)	B 值(K) 25/50°C	额定功率 @25°C (mW)	耗散系数(δ) (mW/°C)	热时间常数 (S)
TS502□3274A	5.0	3274 \pm 1%	10-20	2-4	5-20
TS502□3435B	5.0	3435 \pm 1%			
TS502□3470A	5.0	3470 \pm 1%			
TS502□3950A	5.0	3950 \pm 1%			
TS103□3274A	10.0	3274 \pm 1%			
TS103□3435B	10.0	3435 \pm 1%			
TS103□3470A	10.0	3470 \pm 1%			
TS103□3950A	10.0	3950 \pm 1%			
TS103□4100A	10.0	4100 \pm 1%			
TS153□3950A	15.0	3950 \pm 1%			
TS153□4100A	15.0	4100 \pm 1%			
TS203□3950A	20.0	3950 \pm 1%			
TS203□4100A	20.0	4100 \pm 1%			
TS223□4200A	22.0	4200 \pm 1%			
TS403□3928A	40.27	3928 \pm 1%			
TS503□3950A	50.0	3950 \pm 1%			
TS503□4100A	50.0	4100 \pm 1%			
TS104□3950A	100	3950 \pm 1%			
TS104□4100A	100	4100 \pm 1%			
TS104□4400A	100	4400 \pm 1%			

◆可根据客户要求定做特殊规格。